Palomar Adaptive Optics Test Plan

Title	NGS AO Checkout
Version	3.1
Date released	4/2/2007
Lead	A. Bouchez
Time requested	20 minutes every LGS night. Start after 6° twilight.
Required conditions	N/A

Purpose

Verify acceptable performance of the NGS AO system for subsequent engineering tests, and measuring seeing, on-axis Strehl and isoplanatic angle.

Test procedure

- 1. Slew to a V=7 A star near zenith.
- 2. Verify that AO system is set up for NGS.
- 3. Acquire the primary with the AO system with an initial frame rate of 1000Hz. Adjust the frame rate to get 100-200 cts/subap on the WFS.
- 4. Offset to sky and record a wavefront sensor sky.
- 5. Perform both coarse and fine WFS-DM registration.
- 6. Verify that co default2 is loaded and that focus offloading is on.
- 7. Close the TT and DM loops.
- 8. Create a flat map on the star.
 - 8.1. IDL> ao make dm flat map, filename
 - 8.2. Load the flat map when complete.
- 9. While waiting for the flat map, check signal levels on PHARO:
 - 9.1. Initial setup: 25mas FOV, filter BrG, ND 1%, standard cross, 2s integration.
 - 9.2. Adjust the exposure time and filter to get 10-15k peak counts.
- 10. Open TT and DM loops, offset to sky, and record a new WFS background.
- 11. While on sky, record 3 PHARO sky frames.
- 12. Offset back to star and close TT and DM loops.
- 13. Record 3 images with PHARO. Note the directory, frame numbers, and Strehl.
- 14. Open the DM loop only.
- 15. Record 1 image with PHARO, 30s integration. Note frame number and FWHM.
- 16. Record the telescope focus.

UT date
OT date
Weather conditions
PHARO directory
Target name
13. Sky frames
15. Closed-loop frames
15. Closed-loop Strehl
17. Open-loop frame
17. Open-loop FWHM
18. Telescope focus